




E-able Power Technology Co., Limited

Contact:sales@e-ablepower.com

Tel:+86-18668315797

Skype:tengye.arthur

LED Rechargeable Flood Light

Model	Picture	Specification	Qty/ ctn (pcs)	G.W./ct n (kgs)	Inner box Size (cm)	EXW <100pcs	EXW 101-500pcs	EXW >500pcs
EA -FR-5W		1) Light source: 1*5W Epistar chip 90 LM/W 2) Charging time: 5 hours 3) Working time: 3hours 4) Battery: 7.4V,2200mAh rechargeable Li batteries 5) Input Voltage: 100-240V/AC 6) Dimension: 145x166x225 mm 7) Weight: 1.1kg 8) AC/DC adapter included 9) Carton size : 55*36.5*34 10) IP65 11) Beam angle :120°/140° (Rectangular beam) 12) Color temperture :3000-3500K 5000-5500K	12	15	17.7*17.7*16	USD33.66	USD32.34	USD30.80

EA -FR-10W



- 1) Light source: 1*10W Epistar chip
90 LM/W
- 2) Charging time: 5 hours
- 3) Working time: 3hours
- 4) Battery: 7.4V,4400mAh
rechargeable Li batteries
- 5) Input Voltage: 100-240V/AC
- 6) Dimension: 145x166x225 mm
- 7) Weight: 1.2kg
- 8) AC/DC adapter included
- 9) Carton size : 55*36.5*34
- 10) IP65
- 11) Beam angle :120°/140°
(Rectangular beam)
- 12) Color temperture :3000—
3500K 5000-5500K

12

16.3

17.7*17.7*16

USD42.24

USD42.24

USD38.50



- 1) Light source: 1*20W Epistar chip
90 LM/W
- 2) Charging time: 5 hours
- 3) Working time: 3hours
- 4) Battery: 14.8V,4400mAh
rechargeable Li batteries



- 5) Input Voltage: 100-240V/AC
- 6) Dimension: 215x185x295 mm
- 7) Weight: 2kg
- 8) AC/DC adapter included
- 9) Carton size : 65*41.5*50
- 10) IP65
- 11) Beam angle :120°/140°
(Rectangular beam)
- 12) Color temperture :3000-3500K
5000-5500K

12

27

21*20*24

USD71.17

USD69.19

USD67.32

EA -FR-20W

Main Features:

- 1. With charge protection and dis-charge protection
- 2. Running in constant current
- 3. With charging indicator, When full charged, the red indicator LED will turn to green. When the battery almost run out, the lamp will flash when working
- 4. Wireless / Flexible / Portable
- 5. Housing Color: Red/Green/Yellow/Silver are available
- 6. Warranty: 2 years

