Solar Post Top Lights

E-Able Power · Lishui E-able Power Equipment Co., Ltd · www.e-ablepower.com · arthur@e-ablepower.com

Model	Lumen output	Solar panel	Battery	Size (mm)	IP rating
GGD-001 Solar Post Top Light	822 lm	5V / 20W	3.2V / 20Ah (64Wh)	480 mm × H440 mm	IP65
GGD-002 Solar Post Top Light	778 lm	5V / 20W	3.2V / 20Ah (64Wh)	400 mm × H410 mm	IP65
GGD-003 Solar Post Top Light	1735 lm	5V / 25W	3.2V / 30Ah (96Wh)	530 mm × H490 mm	IP65
GGD-2005 Solar Post Top Light	1377.9 lm	5V / 28W	3.2V / 30Ah (96Wh)	1070 mm × H300 mm	IP65
TYD-1104 Solar Post Top Light	1344 lm	5V / 25W	3.2V / 30Ah (96Wh)	530 mm × H440 mm	IP65
TYD-2403 Solar Post Top Light	1163 lm	5V / 20W	3.2V / 20Ah (64Wh)	400 mm × H420 mm	IP65
TYD-2505 Solar Post Top Light	3539 lm (3000K) / 3636 lm (6500K)	48W / 5V	3.2V / 60Ah (60000mAh)	580 mm × 580 mm × H255 mm	IP65
TYD-2508 Solar Post Top Light	803.54 lm (3000K) / 890.47 lm (6500K)	20W / 5V	3.2V / 20Ah (20000mAh)	415 mm × H385 mm	IP65
TYD-2609 Solar Post Top Light	2650 lm (3000K) / 2758 lm (6500K)	36W / 5V	3.2V / 45Ah (45000mAh)	ϕ585 mm × H550 mm	IP65
TYD-2705 Solar Post Top Light	1270 lm	5V / 20W	3.2V / 20Ah (64Wh)	480 mm × H410 mm	IP65
TYD-2806 Solar Post Top Light	2658 lm (3000K) / 2777 lm (6500K)	36W / 5V	3.2V / 45Ah (45000mAh)	ϕ585 mm × ϕ78 mm × H215 mm	IP65
TYD-4206 Solar Post Top Light	2574.23 lm (3000K) / 2836.6 lm (6500K)	36W / 5V	3.2V / 48Ah (48000mAh)	550 mm × H510 mm	IP65
TYD-4208 Solar Post Top Light	PWM 5105 lm / MPPT 5740 lm (6500K)	62W / 5V	3.2V / 100Ah (100000mAh)	590 mm × 590 mm × H505 mm	IP65

Compliance

CE (EMC / LVD test reports) · IEC-referenced test data · RoHS · ISO 9001 · ISO 14001 · ISO 45001

Parameters on this sheet are taken from the current product page. Warranty terms, packing data and certifications are confirmed per order in the quotation.