**LISHUI E-ABLE POWER EQUIPMENT CO., LTD**
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com
WhatsApp +86 153 5558 9600

DATASHEET · EAP-DS-20261107-512628-R01

# 51.2628

Vertical floor-standing LFP battery · 32.15 kWh · 628 Ah

A 32.15 kWh lithium iron phosphate battery for residential and small commercial storage. It uses a 51.2 628 Ah pack with an integrated BMS, 200 A charging and 200 A continuous discharge, and communicates over RS232, CAN, RS485, WiFi or Bluetooth.

RESIDENTIAL STORAGE | BACKUP POWER | SELF-CONSUMPTION | OFF-GRID CABINS | SMALL COMMERCIAL | MICROGRID



| 32.15 kWh | 628 Ah | > 6,000 | IP21 |
|---|---|---|---|
| RATED CAPACITY | PACK CAPACITY | CYCLES | ENCLOSURE (IP65 OPTIONAL) |

## KEY FEATURES

01
### LFP chemistry
Lithium iron phosphate cells rated for more than 6,000 cycles at 80 % depth of discharge.

02
### 200 A / 200 A
Continuous charge and discharge ratings with an integrated BMS and cell-level monitoring.

03
### Parallel to 15 units
Up to 15 batteries in parallel for larger banks, with automatic address assignment.

04
### Five interfaces
RS232, CAN, RS485, WiFi and Bluetooth; LCD colour screen with optional touch display.

05
### Indoor cabinet
IP21 as standard, IP65 optional, 872 × 530 × 530 mm, 235.2 kg.

06
### Five-year warranty
UN38.3, MSDS, CE, RoHS and FCC documentation supplied with the battery.

## SCOPE OF SUPPLY

- 51.2628 LFP battery
- Integrated BMS
- Communication cable set
- Mounting bracket or base
- UN38.3 / MSDS / CE / RoHS / FCC documents

### APPLICATION NOTE

Size the bank for the night load plus one day of autonomy, and keep the charge current within the pack rating. Parallel strings need equal cable lengths and a common busbar.

**LISHUI E-ABLE POWER EQUIPMENT CO., LTD**
No.368, Chengbei Road, Liandu District, 323000, Lishui City, Zhejiang, China
www.e-ablepower.com | arthur@e-ablepower.com
WhatsApp +86 153 5558 9600

## TECHNICAL SPECIFICATIONS

### BATTERY

| | |
|---|---|
| Model | **51.2628** |
| Standard voltage | **51.2 V** |
| Standard capacity | **628 Ah** |
| Rated capacity | **32.15 kWh** |
| Working voltage | **43.2–57.6 V** |
| Standard charging current | **200 A** |
| Standard discharging current | **200 A** |
| Suggested DOD | **80 %** |
| Cycle life | **> 6,000 cycles** |

### GENERAL

| | |
|---|---|
| Ingress protection | **IP21 (IP65 optional)** |
| Discharge temperature | **−20 to +50 °C** |
| Charging temperature | **0 to +45 °C** |
| Maximum parallel | **15 pcs** |
| Communication | **RS232 / CAN / RS485 / WiFi / BT** |
| Display | **LCD colour screen (touch optional)** |
| Product size | **872 × 530 × 530 mm** |
| Package size | **985 × 640 × 740 mm** |
| Net / gross weight | **235.2 kg / 260.5 kg** |

### COMPLIANCE AND WARRANTY

| | |
|---|---|
| Warranty | **5 years** |
| Certificate | **UN38.3 / MSDS / CE / RoHS / FCC** |
| Packing | **Single export carton** |

## NOTES

- Charge and discharge currents are the standard ratings printed in the source; higher peaks are BMS-limited.
- IP65 is an option and must be specified on the order.
- Packing is described by method only; carton dimensions and gross weight are supplied with the shipping documents.

Specifications are nominal and may change without notice. The contractual revision is the one confirmed in the order acknowledgement. Draft R01 for internal review.